CHEMOTEX Děčín a. s.

Děčín XXXII – Boletice nad Labem 63 407 11 Děčín Czech Republic Tel: +420-412-709 222 Fax: +420-412-547 200

E-mail: chemotex@chemotex.cz

www.chemotex.cz

INDAKOR D

TECHNICAL DATA SHEET TL 162/2001

Date of Issue: 24. 10. 2002 Date of Revision: 12. 1. 2015

Product characteristics

INDAKOR D is boric acid amino ester.

Applications

INDAKOR D is used as an anti-corrosion additive.

Product Features

INDAKOR D is colourless to flavescent coloured viscous liquid.

INDAKOR D must comply with the following quality characteristics:

| Quality characteristic | Value | Methodology of assessment |
|-----------------------------|---------------|---------------------------|
| Total alkalinity (mg KOH/g) | minimally 400 | PN-ZM 162/2001 |
| pH of a 1% aqueous solution | maximally 10 | PN-ZM 162/2001 |

Directions for Use

INDAKOR D has outstanding anti-corrosion and bacteriostatic properties, especially in case of fully synthetic products.

INDAKOR D is used as an anti-corrosion additive for:

- Synthetic abrasive cooling fluids
- Cooling lubricant agents
- Hydraulic fluids
- Degreasing baths

The product is water soluble, miscible with surfactants and finitely miscible with mineral oils. These properties are premises for use in the mentioned applications.

Recommended dosage is from 0.5 to 2 %. The effective concentration of **INDAKOR D** must be adjusted in accordance to application conditions and experimentally verified in advance.

Packaging & Storage

INDAKOR D is delivered in 50 l PE bottles. Alternatively, it can be delivered in different containers that were discussed and agreed on in advance. Store it in a sealed container in places protected from direct climatic influences. Recommended storage temperature is between +5 to +25 °C. Storing at temperatures below 0 °C does not affect product's application properties.

<u>Transport</u>

INDAKOR D is transported by covered vehicles. It is not subject to ADR/RID Regulations.

Warranty

Provided the product is transported and stored in accordance with the above written conditions, its warranty is 6 months from the production date.

| Note Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical data sheet can provide solely legal advice without any engagements. Use of the product should be always adjusted to specific conditions. | | |
|--|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |