

CHEMOTEX Děčín a. s.

Děčín XXXII – Boletice nad Labem 63
407 11 Děčín
Czech Republic

Tel: +420-412-709 222

Fax: +420-412-547 200

E-mail: chemotex@chemotex.cz
www.chemotex.cz

EBOL ORVK

TECHNICAL DATA SHEET

TL 393/2005

Date of Issue: 15. 7. 2005

Date of Revision: 27. 8. 2014

Product characteristics

EBOL ORVK is an aqueous solution of mixture of organic and inorganic acids and surfactants.

Applications

EBOL ORVK is highly efficient cleaning and degreasing agent that removes rust and limescale. The product removes even deeply sedimented dirt quickly and without any difficulties, and it leaves a cleaned surface clean and shiny. It is ideal for brass, stainless and ceramic sinks, water and shower taps, bathtubs, toilets, spouts, linings and glass and plastic surfaces.

Product Features

EBOL ORVK is blue coloured liquid that can be mixed with water in any ratio.

EBOL ORVK must comply with the following quality characteristics:

| Quality characteristic | Value | Methodology of assessment |
|-----------------------------|--------------|---------------------------|
| Dry matter (%) | minimally 21 | PN-ZM 393/2005 |
| pH of a 1% aqueous solution | 1.5 to 2.5 | PN-ZM 393/2005 |

Directions for Use

Appropriate quantity of **EBOL ORVK** should be poured on a cleaned surface or a cleaning sponge and the surface should be wiped several times. Products made of chrome, enamel and stainless steel should be treated with the agent in a diluted state. The agent should be allowed to act for 2 to 5 minutes. Afterwards, the cleaned surface needs to be thoroughly rinsed with clean water. In case of heavy soiling, we repeat the procedure; alternatively, we allow the agent to react for a longer time.

Recommended dilution: 1 unit of **EBOL ORVK** should be diluted by 2 to 4 units of water.

The agent is classified as an irritant. Consequently, personal protective equipment, especially protective gloves, must be used when working with it or using it.

Packaging & Storage

EBOL ORVK is delivered in 50 l PE cans. Alternatively, it can be delivered in different containers that were discussed and agreed on in advance. Store it in a sealed container in places protected from direct climatic influences. Recommended storage temperature is between +5 to +25 °C. Short-term exposure to lower temperatures, e.g. during transport, does not affect product's application properties.

Transport

EBOL ORVK is transported by covered vehicles. It is not subject to ADR/RID Regulations.

Warranty

Provided the product is transported and stored in accordance with the above written conditions, its warranty is 6 months from the date it was delivered from a warehouse.

Note

Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical data sheet can provide solely legal advice without any engagements. Use of the product should be always adjusted to specific conditions.