

**CHEMOTEX Děčín a.s.**  
Tovární 63  
407 11 Děčín XXXII - Boletice n. L.  
Czech Republic

**Tel: +420-412-709 222**  
**Fax: +420-412-547 200**  
**E-mail: chemotex@chemotex.cz**  
**www.chemotex.cz**

## KORYNT SUELO

### TECHNICAL DATA SHEET TL 353/2004

Date of issue: 17.05.2004

Revision date: 09.05.2012

#### **Product characteristics**

**KORYNT SUELO** is an alkaline washing and degreasing preparation.

#### **Use**

It is used for the washing of motor vehicles and tram cars. It can be also used for a machine- and hand-washing of severely dirty surfaces, especially floorings. It is suitable for the following surfaces – PVC, plastics, imitation leathers, glazed and non-glazed tiles, enamelled and varnished surfaces, teraco, stone, plastic-concrete surfaces, formica, etc.

#### **Product features**

**KORYNT SUELO** is a low-viscous, yellowish liquid miscible with water in any proportions

**KORYNT SUELO** must comply with these quality signs:

Quality sign	Value	Methodology of setting
Dry matter content (%)	6,5 minimum	PN-ZM 353/2004
Aqueous solution 3% pH	10,0 up to 11,5	PN-ZM 353/2004

#### **Product manufacturing**

So called **Varnish-resistant system test - test of the product influence on the crater creation (crater-test)** was carried out in terms of **KORYNT SUELO**. The preparation was found negative with regard to varnished surfaces.

Protocol no. 23/824/2006 Hv. was issued to inform about this test - can be sent if requested. Cleanser **KORYNT SUELO** is dosed in dependence on the type of washing equipment and in accordance with a surface dirtiness level.

#### **Washing motor vehicles and tram cars**

	<b>Dilution ratios</b>
Car washes	1:50 up to 1:200
Hand washing	1:20 up to 1:100
Washing under pressure	1:50 up to 1:200
Insects removal	1:5 up to 1:10
Car rims	1:10 up to 1:50

TIR washes	1:50 up to 1:200
Tram washes	1:50 up to 1:200
Interiors - plastics, upholstery, leather and imitation-leather surfaces	1:50 up to 1:300
Chromed vehicle parts	1:50 up to 1:200

### **Washing of surfaces and flats**

The recommended dilution is 1:1 up to 1:100

	<b>Dilution ratio</b>	<b>Time of functioning</b>
Severe dirtiness	1:1	2 to 6 minutes, eventually longer if needed
Moderate dirtiness	1:2 to 1:10	2 to 6 minutes
Light dirtiness	1:10 to 1:100	No need to keep functioning

### **Packing and storage**

**KORYNT SUELO** is delivered in PE cans (25 litres or 50 litres) or in other packages that have been discussed in advance. This product is stored in closed containers at the places protected from direct weather influences. The recommended storage temperature is between +5 to +25 °C.

### **Transport**

**KORYNT SUELO** is transported in covered vehicles and is not subject to the ADR/RID regulations.

### **Warranty**

If the product is transported and stored according to the above mentioned conditions, the warranty is 6 months from the date of stock-out.

### **Note**

Data about the product characteristics and its manufacturing were acquired by laboratory measurements and application tests. This technical sheet can only give a legal advice without any obligation. The manufacturing of the product must be adjusted to the specific conditions.

Chemotex