

CHEMOTEX Děčín a. s.
Děčín XXXII – Boletice nad Labem 63
407 11 Děčín
Czech Republic

Tel: +420-412-709 222
Fax: +420-412-547 200
E-mail: chemotex@chemotex.cz
www.chemotex.cz

KORYNT CLEANER

TECHNICAL DATA SHEET

TL 603/2011

Date of Issue: 12. 4. 2011

Date of Revision: 12. 3. 2015

Product characteristics

An aqueous solution of surfactants and auxiliary substances with addition of a perfume composition.

Applications

The product is highly concentrated and effective cleaning and degreasing agent intended for industrial use. It is used for cleaning with spraying cleaning machines as well as for pressure and ultrasonic cleaning and degreasing in industrial and tertiary sphere.

The agent is able to replace the following during a cleaning and degreasing process:

- ✓ Chlorinated hydrocarbons (perchloroethylene, trichloroethylene)
- ✓ Alkali hydroxides (sodium hydroxide, potassium hydroxide)
- ✓ Organic aromatic solvents (toluene, acetone, xylene)
- ✓ Benzine

Product Features

KORYNT CLEANER is moderately viscous flavescent coloured liquid. The agent can be mixed with water in any ratio.

KORYNT CLEANER must comply with the following quality characteristics:

Quality characteristic	Value	Methodology of assessment
Density at 20 °C (kg.m-3)	1015 to 1025	PN-ZM 603/2011
pH of a sample	7 to 9	PN-ZM 603/2011

Directions for Use

KORYNT CLEANER is non-flammable, non-abrasive and does not contain colourants, Teflon and silicones. This highly concentrated mixture can be diluted with cold water up to ratio 1:200. After the product is diluted, it cleans and degreases with optimal efficiency even at common working temperatures ranging from 18 to 22 °C which considerably contributes to energy saving!

Possible means of application:

- ✓ Washing by hand
- ✓ Pressure cleaning
- ✓ Submersion washing
- ✓ Washing in ultrasonic dishwashers
- ✓ Filling for floor washing machines

Recommended concentration of working solutions

Spraying degreasing machines	1.0 - 3.0 %
Pressure and ultrasonic washing	0.5 - 3.0 %
Washing by hand	1.5 - 5.0 %

Packaging & Storage

KORYNT CLEANER is delivered in 50 l PE bottles. Alternatively, it can be delivered in different containers that were discussed and agreed on in advance.

Store it in a sealed container in places protected from direct climatic influences. Recommended storage temperature is between +10 to +25 °C.

Transport

KORYNT CLEANER is transported by covered vehicles. It is not subject to ADR/RID Regulations.

Warranty

Provided the product is transported and stored in accordance with the above written conditions, its warranty is 6 months from the production date.

Note

Data about the product characteristics and its processing were obtained by laboratory measurements and application tests. This technical data sheet can provide solely legal advice without any engagements. Use of the product should be always adjusted to specific conditions.